



- 1 Type**
- ST** Plastic (KT)
Technopolymer (Polyamide PA)
 - SK** Plastic (KU)
Duroplast (PF)

d ₁	d ₂	Length l ≈ GN 6336.4										Length l ≈ GN 6336.5										d ₃	h ₁	h ₂
		Type ST										Type SK												
25	M 5	10	15	20	25	30	-	-	-	-	-	-	-	-	10	15	20	25	-	12	16	8		
32	M 6	10	16	20	25	30	35	45	60	16	20	25	30	35	45	10	16	20	25	30	14	20	10	
40	M 8	16	20	25	30	35	40	50	55	16	20	25	30	40	55	20	25	30	40	-	18	25	13	
50	M 10	15	20	25	30	35	40	45	55	25	30	35	45	55	-	20	25	30	45	55	22	32	17	
63	M 12	20	25	30	35	40	50	60	-	30	35	40	50	60	-	30	40	50	-	-	26	40	21	
80	M 16	-	-	-	-	-	-	-	-	30	40	50	60	70	-	-	-	-	-	-	35	50	25	

Specification

- **GN 6336.4**
 - Threaded bolt
Steel
zinc plated, blue passivated
 - Knob (Type ST)
Technopolymer (Polyamide PA)
shock-resistant
black matte
 - Knob (Type SK)
Duroplast
black shiny

- **GN 6336.5**
 - Threaded bolt
Stainless Steel
M6... M10: AISI 304 Cu
M12: AISI 303
 - Knob (Type ST)
Technopolymer (Polyamide PA)
shock-resistant
black matte

- *Plastic characteristics* → Page 1141
- *Stainless Steel characteristics* → Page 1144
- **RoHS compliant**

Information

Star knobs GN 6336.4 / GN 6336.5 comply with DIN 6336 type L.

see also...

- *Star knobs GN 6336.10 (with brass / plastic pivot)* → Page 282
- *Star knobs GN 6336.12 (with movable thrust pad)* → 283
- *Star knobs GN 6336.13 (with loss protection)* → New Products
- *Star knobs GN 6336.4 with loss protection GN 111.7* → Page 278

How to order (Threaded bolt steel)

GN 6336.4-SK-32-M6-25

1	Type
2	d ₁
3	d ₂
4	Length l

How to order (Threaded bolt St. Steel)

GN 6336.5-ST-63-M12-60

1	Type
2	d ₁
3	d ₂
4	Length l