	ety Data Sheet		U.S. Department of Labor					
May be used to	comply with				Occupational Safety and Health Administration			
	d Communication St				(Non-Mandatory Form)			
29 CFR 1910,1200. Standard must be					Form Approved			
consulted for specific requirements					OMB No. 1218-0072			
Identity (As used on Label and List)					Note: Blank spaces are not permitted. If and item			
Kolor Kut Gasoline Gauging Paste ® 2.25 oz. jar					is not applicable, or no information is available, the space must be marked to indicate that.			
Section l	C-C-14 VAII	J**·	T share must be ill	SIVED (O HIDICATA	uiat.			
Manufacturer's Name Emergency Telephone Number								
Kolor Kut ® Products Co., Ltd.					713-926-4780			
Address (Number, Street City, State and ZIP Code)					Telephone Number for Information			
7915 East Elm Street					713-926-4780			
Houston, TX 77	012		Date May 9, 2012					
Kolor Kut Gasoli	ne Gauging Paste®		Signature of Preparer (optional)					
Kolor Kut® is a r	egistered trademark o	Kolor Kut I	_D. Frauenberger					
Section II – Hazardous Ingredients/Identity Information								
Hazardous Com	ponent			OSHA PEL	ACGIH TLV	Other Limits	%	
	Identity: Common Nar	ne(s)				Recommende		
NONE								
All Ingredients Non-Hazardous								
					**			
Section III - Physical / Chemical Characteristics								
Bolling Point				212 Degrees F.	Specific Gravity	· · · · · · · · · · · · · · · · · · ·	1	
Vapor Pressure	/asas I la V			61/6	(H2O=1)			
yapor Fressure	(mm rg.)	İ		N/A	Melting Point		120 DegreesF	
Vapor Density (AIR=1)			N/A	Evaporation Rate		N/A		
					(BUTYL ACETATE=1)			
Solubility in Water Yes								
Appearance and	Odor			-, 				
	t Pink Semisolid							
Section IV -	 Fire and Explos 	ive Haza	ard Da	<u>ita</u>				
Flash Point (Method Used)					Flammable Limits	I		
none N/A N/A N/ Extinguishing Media							N/A N/A	
Standard dry chemical, foam, co-2, water-fog								
Special Fire Fighting Procedures								
Wear a NIOSH /MSHA approved self contained breathing apparatus and full protective clothing.								
	containers exposed to	ofire with w	ater.					
	d Explosion Hazards							
-None								
Stability	Unstable		Conditions to Avoid					
Ctability	Charane		Conditions to Avoid					
	Stable	XXXX	None	Known				
	Andread de Arrivol							
Incompatibility (Material to Avoid) Oxidating agents & acids								
Hazardous Decomposition or Byproducts								
None Known								
Hazardous Polymerization	May Occur		Condi	tions to Avoid	Į			
, , , , , , , , , , , , , , , , , , , ,	Will Not Occur	XXXXX	None	Known	14			
I	ì	i						

-1-

Kolor Kut Gasoline Gauging Paste ®
Kolor Kut ® is a registered trademark of
Kolor Kut ® Products Company, Ltd.
Houston, Texas USA

Section VI - Healt			lumin alton 0						
Routes(s) of Entry:	inhalation?	Skin?	Ingestion?						
None known at normal temperature. Mild irritation									
Health Hazards (Acute a	nd Chronic)								
None Known at this time. If Ingested, induce vomiting immediately by giving 2 glasses of water and sticking finger down throat.									
If Ingested, in	luce vomiting immediately by giving 2 gir	BSSBS OF MATER BITC SUCKING	inigor down iniodal						
4 15	NTP?	IARC Monographs'	OSHA Regulated?						
Carcinogenticity:	IN IF I								
This product does not contain any ingredient designated by larc, ntp, aoglin or osha as a									
known human carcinogen. Signs and Symptoms of Exposer									
Imitation and bad odor.									
(())Control Circ									
Medical Conditions Gen	erally Aggravated by Exposure								
Not Determined									
Emergency and First Air	i Procedures	1. Taille and description of possible	olo						
Eyes: use eyewash fountain, get medical attention if irritation developes or persists. Skin: use clean cloth wash w / soap & water. Inhalation- seek medical attention.									
Skin: use cle	an cloth - wash w / soap & water, Innaia	iiou- seek Meoinsi ariennoi	omatically						
Ingestion: in	luce vomiting-seek medical attention. No	NG to bilikaloigh, mear aymbi	Officialisti						
2 11 111 5	where for Cafe Handling on	d Ugo							
Section VII - Pre	cautions for Safe Handling and	7 096							
Steps to Be Taken In C	ase Material is Released or Spilled	roprieto containet							
Unlikely, co	ntain splil, wipe up, and dispose into app	inhigre contractor:							
Waste Disposal Metho	4	1-							
Dispose of	n accordance with local, state and feder	al regulations.							
D/dp004 4.1									
Precautions to Be Tak	en in Handling and Storing								
Store at roo	m temperature do not expose to high ter	nperatures or water contam	ination.						
D	/for propopution of product only)								
Avoid proid	nged contact with with skin. Wash hands	thoroughly after handling,	DO NOLTOD BYES WILL SCHOOL HANDS.						
		<u> </u>							
Other Precautions									
None Known									
O Car VIII C	antrol Magruros								
Section VIII - Control Measures									
Respiratory Protection (Specific Type) No special respiratory protection required,									
			Special						
	al Exhaust		Maintain safety equipment.						
	e local exhaust as needed.		Other						
	chanical (General)		N/A						
Heatosthia Glovos	1		ve Protection						
Protective Gloves Recommended if desired or as required Recommended if desired or as required Safety glasses with side s									
Other Protective Clothing or Equipment									
Work clothing									
Work/Hygienic Pract	Work/Hyrainic Practices								
Ве Clean, а	Be Clean, after applying, clean hands with soap and water.								

-2-

Kolor Kut Gasoline Gauging Paste ®
Kolor Kut ® is a registered trademark of
Kolor Kut ® Products Company, Ltd.
Houston, Texas USA