

Q21.0014 del 18/11/2021 – DATASHEET

Pos.	Item
1	<p>new p/n MASES1504NS1AM000001</p> <p>Description: DEHYDRATING BREATHERS COMEM eSDB15 VOLTAGE 230 V DC/AC CONNECTION : FLANGE TYPE DN40 IP45 (ELECTRICAL BOX IP65) CORROSION PROTECTION: CATEGORY C4 RAL7032 GASKETS: NBR -40°C/+120°C OUTPUT: 4-20mA MODBUS DATA LOGGER OVERVOLTAGE PROTECTION WITH DAMPER CABLE GLAND: M25x1.5 TYPE OF PACKING: WOOD BOX</p>
2	<p>new p/n MACTKWTI4NEF0C6LD000</p> <p>Description: WINDING TEMPERATURE IND. COMEM WTI IEC60076-22-1 DEGREES OF PROTECTION: IP 66 CORROSIVITY CATEGORY: C4 MECHANICAL CONN.:FLANGE SCALE: 0°C/150°C DIAL DIVISION: 5°C RILSAN CAPILLARY PROTECTION CAPILLARY LENGTH: 6m BULB CONN.:3/4"BSP FIG.1: FEM. B. LENGTH: L=150 STANDARD SWITCH TWO SWITCHES PLASTIC VENTILATION VALVE 2 PLASTIC CABLE GLAND M25x1.5, 1 CAP GLASS MULTILAYER DIAL WITH MAX POINTER CT RATED CURRENT: 1 A RAL 7032</p>